



Listino prezzi 2010/ Commercial Series

(iva esclusa 20%)

CM141CC



- > Coax mounted PRD100 ribbon on 4" woofer in a 5" cubical enclosure
- > Barrier strip inputs
- > 8 Ohm only
- > Optional J-Box for wiring (4) units for 8 ohm or 70V, 160W tap operation
- > 100Hz to 20,000Hz Operating Range
- > 110 Deg Conical Dispersion
- > Recommended amplifier power: 100W @ 8 Ohms
- > Maximum Calculated SPL @ 1 meter Continuous Output: 102dB
- > 12.7cm cube enclosure, 1.6kg (each), Shipping Weight 3.63kg (pair)



MNT.CM141CC

CM141CC-BK
(High Gloss Black Finish)

euro _____
261,00 cp.

CM141CC-WT
(High Gloss White Finish)

261,00 cp.

MNT.CM141CC-BK
(Optional Mounting bracket-black)

36,00.

MNT.CM141CC-WT
(Optional Mounting bracket-white)

36,00.

CM832.JB
(Optional Impedance matching J-box)

63,00.

CM208W



- > Dual 8" Subwoofer
- > 8 Ohms or Optional internal factory installed 70V transformer (set 60W tap)
- > Includes passive crossover with high pass series/parallel outputs (min. 2, max 8 HP spkrs)
- > Bi-amp capable between sub and series/parallel outputs (up to (8) 8 ohm satellites per sub)
- > (16) 3/8"16 inserts for rigging
- > 33Hz to 200Hz Operating Range
- > Recommended amplifier power: 400W @ 8 Ohms for subwoofer and (4) 8 ohm satellites
- > Maximum Calculated SPL @ 1 meter Continuous Output: 112dB
- > 27cm H, 62.5cm W, 46cm D, 21.77kg, Shipping Weight 28.6kg

CM208W-BK
(Black Finish)

euro _____
639,00

CM208W-WT
(White Finish)

639,00

TRANS.CM208W
(Optional internal 70V, 60W transformer)

126,00

Listino prezzi 2010/ Commercial Series

(iva esclusa 20%)

CM208W-TB



- > Dual 8" Subwoofer for ceiling tile installations, includes install ring and white grill
- > 8 Ohms or Optional internal factory installed 70V transformer (set 60W tap)
- > Painted with a Class A fire rated finish
- > Includes passive crossover with high pass series/parallel outputs (min. 2, max 8 HP spkrs)
- > Bi-amp capable between sub and series/parallel outputs (up to (8) 8 ohm satellites per sub)
- > Included installation ring that can be shipped in advance of unit, part "ASSY.CM208C-MR"
- > 32Hz to 200Hz Operating Range
- > Recommended amplifier power: 400W @ 8 Ohms for subwoofer and (4) 8 ohm satellites
- > Maximum Calculated SPL @ 1 meter Continuous Output: 112dB
- > 48.3cm L, 48.3cm W, 40cm D, 20.4kg, Shipping Weight 28.6kg

	euro
CM208W-TB (Price includes required ASSY.CM208C-MR install ring)	693,00
ASSY.CM208C-MR (Required install ring, please order 1 with each sub and note if advance shipment is required)	-
TRANS.CM208W (Optional internal 70V, 60W transformer)	126,00

CM208W-SR



- > Dual 8" Subwoofer for sheetrock installations, includes install ring and white grill
- > 8 Ohms or Optional internal factory installed 70V transformer (set 60W tap)
- > Painted with a Class A fire rated finish
- > Includes passive crossover with high pass series/parallel outputs (min. 2, max 8 HP spkrs)
- > Bi-amp capable between sub and series/parallel outputs (up to (8) 8 ohm satellites per sub)
- > Included installation ring that can be shipped in advance of unit, part "ASSY.CM208C-MR"
- > 32Hz to 200Hz Operating Range
- > Recommended amplifier power: 400W @ 8 Ohms for subwoofer and (4) 8 ohm satellites
- > Maximum Calculated SPL @ 1 meter Continuous Output: 112dB
- > 48.3cm L, 48.3cm W, 40cm D, 20.4kg, Shipping Weight 28.6kg

	euro
CM208W-SR (Price includes required ASSY.CM208C-MR install ring)	693,00
ASSY.CM208C-MR (Required install ring, please order 1 with each sub and note if advance shipment is required)	-
TRANS.CM208W (Optional internal 70V, 60W transformer)	126,00

Listino prezzi 2010/ Commercial Series

(iva esclusa 20%)

PRD8COM



- > Passive Two-Way ceiling speaker with an 8" LF, and a 3" Ribbon
- > Typical ceiling cutout of 12.25"
- > 70V taps at 7.5W, 15W, 30W and 60W
- > 8 Ohm by-pass
- > 45Hz to 25,000Hz Operating Range (w/optional 1 cu. ft backbox)
- > 120 Deg Horizontal Dispersion, 90 Deg Vertical Dispersion
- > Recommended amplifier power: 200W @ 8 Ohms (bypassed transformer)
- > Maximum Calculated @ 1 meter Continuous Output: 114dB (bypassed transformer)
- > Baffle diameter of 27.3cm, above ceiling vertical clearance 11.4cm 4.5kg
- > With BBOX.5 option, above ceiling vertical clearance 20.3cm 6.4kg
- > With BBOX option, above ceiling vertical clearance 26.7cm 8.2kg

	euro
PRD8COM (No Backbox, white grill)	504,00
PRD8COM.BBOX (1cu. ft Backbox and a pair of 24" channel rails)	90,00
PRD8COM.BBOX.5 (.5cu. ft Backbox and a pair of 24" channel rails)	72,00
PRD8COM.TB (Optional Tile Bridge for either .5 or 1 backbox)	18,00

distribuito in Italia da :

KENNEL Sas

Corso Unione Sovietica 324 - 10135 TORINO tel. 011 614342 - 011 612148 web : www.kennell.it mail : kennell@kennell.it